



VRX 00 220

VRX00220 22,68Qli / 5.000 lb 12 volt

Specifiche: Features:

Forza trazione Rated line pull	5000 lbs(2268kgs)
Motore Motor	Permanent magnetic 2,76KW/3,68hp(12V);4,32KW/5,76hp(24V)
Rapporto cambio Gear reduction ratio	294:1(12VDC), 210:1(24V)
Cavo lun. Cable(Dia.*L)	Ø1/4"*79'(Ø6mm*24m)
Misura tamburo lun. Drum size(Dia.*L).	Ø2.48"*5.5"(Ø63mm*140mm)
Dim.totali lun.lar.alt. Overall dimensions(*L*W*H)	17.3"*7.1"*6.8"(440mm*180mm*173mm)
Dim.totali lun.lar.alt. Overall dimensions(*L*W*H)	17.3"*7.1"*10.63"(440mm*180mm*270mm)(Up-Setting Type)
Struttura montaggio Mounting bolt pattern	6.55"*4.5"(166.4mm*114.3mm)
Peso Weight	52.9 lbs(24kgs)

Peso 56.2 lbs(25.5kgs)(Up-Setting Type)
Weight

Trazione, velocità, ampere, volts (1a tensione) Pull, Speed, Amperes, Volts(First layer)

Trazione (libr.Kg.) Line Pull Ibs(kgs)	Velocità piedi/min (m/min) Line Speed ft/mit(m/min)	Corrente Current A	12V DC	24V DC
0	12.0(3.7)	45	12V DC	24 VDC
1000(454)	10.0(3.2)	90		
3000(1361)	7.5(2.3)	150		
5000(2268)	5.0(1.5)	230		

Trazione e portata corda in tensione Line Pull And Rope Capacity In Layer

Tensione corda Layer	Forza trazione Rated Line Pull Ibs(kgs)	Corda totale su tamburo Total Rope On Drum ft(m)
1	5000(2268)	14.7(4.5)
2	4200(1905)	29.5(9.0)
3	3700(1678)	56.0(17.0)

Avviso: Caratteristiche Standard, non usare per trasporto persone..

Notice: Standard features do not use for people carriage.