



## VRX 00 250

**VRX00250 43,09 Qli / 9.500 lb 12 volt**

### Specifiche: Features

Forza trazione  
Rated line pulle 9500 lbs(4309kgs)

Motore  
Motor Series wound 4.2KW/5.5hp(12V);5.5KW/7,5hp(24V)

Rapporto cambio  
Gear reduction ratio 233:1(12V, 24V)

Cavo lun.  
Cable length Ø3/8"\*85'(Ø9.2mm\*26m)

Misura tamburo lun.  
Drum size(Dia.\*L). Ø2.48"\*9"(Ø63mm\*228mm)

Dim.totali lun.lar.alt.  
Overall dimensions(\*L\*W\*H) 21.46"\*6.30"\*9"(545mm\*160mm\*220mm)

Struttura montaggio  
Mounting bolt pattern 10"\*4.5"(254mm\*114.3mm)

Peso  
Weight 68.3 lbs(31kg)

### **Trazione, velocità, ampere, volts (1a tensione) Pull, Speed, Amperes, Volts(First layer)**

Trazione (libr.Kg.) Line Pull lbs(kgs)	Velocità piedi/min (m/min) Line Speed ft/mit(m/min)	Corrente Current A
---	--	-----------------------

	12V DC	24 VDC	12V DC	24 VDC
0	22.05(6.8)		65	
2000(907)	11.67(3.6)		179	
3000(1361)	10.05(3.1)		203	
6000(4082)	9.08(2.8)		286	
8000(2722)	7.13(2.2)		330	
9500(4309)	6.16(1.9)		365	

**Trazione e portata corda in tensione Line Pull And Rope Capacity In Layer**

Tensione corda Layer	Forza trazione Rated Line Pull Ibs(kgs)	Corda totale su tamburo Total Rope On Drum ft(m)
1	9500(4309)	18(5.5)
2	7600(3447)	39.4(12)
3	6200(2812)	64(19,5)
4	5400(2449)	85.0(26.0)

**Avviso: Caratteristiche Standard, non usare per trasporto persone..**

**Notice: Standard features do not use for people carriage.**